



PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 :

H04N 7/01

A1

(11) International Publication Number:

WO 93/15586

(43) International Publication Date:

5 August 1993 (05.08.93)

(21) International Application Number: PCT/US93/00808

(22) International Filing Date: 29 January 1993 (29.01.93)

(30) Priority data:
829,202 3 February 1992 (03.02.92) -US

(71) Applicant: EASTMAN KODAK COMPANY [US/US]:
343 State Street, Rochester, NY 14650 (US).

(72) Inventor: LOVERIDGE, Jennifer, Clare : 2 Laura Court,
187 Headstone Lane North, Harrow, Middlesex HA2
6NR (US).


(74) Agent: WOODS, David, M.: 343 State Street, Rochester,
NY 14650-2201 (US).

(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: A PARTIAL INTERPOLATION METHOD AND APPARATUS FOR FRAME RATE CONVERSION



(57) Abstract

A frame rate converter is provided for use in film scanning apparatus of the type wherein pixels relating to input images derived from consecutive frames of film are sampled at a predetermined rate related to a film scanning speed, and wherein output pixel information is converted to output fields of a standard television signal. A frame store (18) holds input image pixel data corresponding to at least two consecutive frames of film (1, 2). Every fifth output field (3) is obtained by accessing the consecutive frames (1, 2) in the frame store (18) and interpolating between image pixel data, specifically by calculating an unweighted inter-frame average of the corresponding lines in the consecutive frames. Thereafter, a standard television signal is generated from the interpolated fifth field (3) and the intervening uninterpolated fields (1, 2, 4, 5).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union -
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

A PARTIAL INTERPOLATION METHOD AND APPARATUS
FOR FRAME RATE CONVERSION

Field of the Invention

5

This invention relates to signal processing apparatus for converting the repetition rate of an image signal from a motion picture frame scanning rate to a television field scanning rate.

10

Background Art

In an electronic imaging system which is concerned with a time-varying sequence of images, it may be necessary to have different input and output frame rates. A typical film-to-video frame rate conversion is from a 24 film frames per second input signal to a 30 video frames per second (or 60 fields per second, interlaced) output signal. This is a requirement, for example, when the input medium is motion picture film and the output signal is displayed on a television monitor operating according to a NTSC television standard, that is, 525 lines/frame and 30 frames (60 fields)/second.

The following three known methods of frame-rate conversion may be used to obtain the necessary conversion:

(1) The so-called "3,2" method is the most commonly used method in current telecine film scanners to obtain a 60 field per second interlaced television output from a 24 frame per second film input. This method is illustrated in Figure 1, which shows the replication of one in every four output fields. More particularly, a five field sequence is generated in which the first two fields are generated from the odd lines and the even lines of the first film frame, the third field repeats the odd lines (or the even lines) of the first film frame, and the remaining two fields are generated from the odd lines and the even lines of the

second film frame. In other words, two or three output fields are generated alternately from each input frame. This produces the required frame-rate conversion but also leads to objectionable temporal artifacts, notably motion-judder.

5 U.S. Patent No. 4,205,337, "Television Film Scanner", generally discloses a telecine scanner utilizing paired field stores to convert a line sequential scan into interlaced fields in the aforementioned(3:2) manner.

(2) Full interpolation between fields may be used to
10 generate five output fields for every two input film frames. This has the advantage of overcoming the motion-judder inherent in the "3,2" method by creating sequential fields which are placed correctly in time. However, motion blur or image ghosting artifacts are produced in areas of image
15 motion. Furthermore, in order to minimize the trade-off between loss of sharpness and temporal aliasing artifacts it is required that the interpolation filter should have a large number of taps, and, due to the resulting framestore requirements, this method is expensive to implement in
20 hardware. An example of this type of interpolation circuit is disclosed in U.S. Patent No. 4,607,282, "Television Circuit for the Reduction of Flicker on a Display".

(3) Frame rate conversion methods employing motion-compensation implement temporal interpolation in a direction
25 determined by a motion vector field. The motion vectors may be generated by several methods including block-matching and phase correlation. Effective motion-compensated algorithms are computationally complex and difficult to implement at high speed in hardware. In addition, they may suffer from
30 noticeable failure in cases where motion vectors are incorrectly determined, for example at occlusion boundaries. Such methods are described in "The development of an HDTV to PAL standards converter and its picture quality", by T. Ohmura, Y. Tanaka, and T. Kurita, IBC Conference
35 Proceedings, 1986, and in "European approaches and prospects on HDTV standards conversion", by D. Nasse, Symposium Record

of 16th International TV Symposium, Montreux, Switzerland, 17-22 June 1989, pp. 472-483.

Clearly, it would be desirable to find a design approach that balances computational complexity and
5 implementation speed, on the one hand, while minimizing image artifacts such as motion judder, loss of sharpness, temporal aliasing, and motion failures, on the other.

Summary of the Invention

10

The invention strikes a reasonable compromise between complexity and artifacts by using linear interpolation to generate every fifth field in the aforementioned five field sequence(i.e., every five consecutive fields are derived
15 from every two consecutive film frames). Accordingly, frame rate conversion apparatus is provided for use in film scanning apparatus of the type wherein pixels relating to input images derived from consecutive frames of film are sampled at a predetermined rate related to a film scanning
20 speed, and wherein output pixel information is converted to output fields of a standard television signal. A frame store holds input image pixel data corresponding to at least two consecutive frames of film. Periodically, an output television field is obtained by accessing image pixel data
25 stored in the frame store and interpolating between corresponding odd (or even) lines in selected input frames. Thereafter, a standard television signal is generated from the interpolated field and the intervening uninterpolated fields.

30 Generally, in terms of a method, the conversion is from an even number of input frames to an odd number of output fields, comprising the steps of generating a first even number of output fields from a first input frame, interpolating an intermediate field from first input frame
35 and a second input frame, and generating a second even number of output fields from the second input frame. More

specifically the conversion is from two input frames to five output fields, wherein the intermediate field is an interframe average of corresponding lines of the two input frames.

5

Brief description of the Drawings

The prior art and the invention will be described in relation to the drawings, wherein

10 Figure 1 is a time sequence diagram of a known technique for frame rate conversion;

Figure 2 is a block diagram of a frame rate conversion apparatus incorporating partial interpolation in accordance with the invention; and

15 Figure 3 is a time sequence diagram of the partial interpolation performed by the apparatus of Figure 2.

Description of the Preferred Embodiment

20 A signal processing channel for use in a telecine film scanner for frame rate conversion in accordance with the invention is shown in block form in Figure 2. A film scanner
10 develops image pixel data corresponding to image pixel areas on a motion picture film. A preferred film scanner 10
25 is described in U.S. Patent No. 5,045,932, "Method and Apparatus for Generating A High Definition Electronic Image Signal from a Line Scan of a Color Original," which is incorporated herein by reference. The signal processing
channel comprises an analog-to-digital (A/D) converter 12, an
30 input image store 14, a spatial interpolator 16, an output image store 18, and a frame rate interpolator 20. A
controller 22 provides system timing for pipelined operation according to the scanning speed of the film scanner 10 and
the television standard in use. Film pixel data from the
35 film scanner 10 is converted to digital pixel data by the A/D converter 12 and applied to the input image store 14 at

a real-time, synchronous rate determined by the controller 22.

The store 14 is capable of storing all of the pixels of at least one complete film frame. Since a preferred application, as set forth in the afore-mentioned '932 patent, is for generation of effects in connection with a HDTV signal, about 1600 lines of film information are stored when scanning a 35mm Academy format motion picture film. This is more than the 1035 active lines which are required for the proposed 1125-line HDTV standard because of the aspect ratio difference of the film and HDTV systems. While not an integral part of this invention, the spatial interpolator 16 can be used in television standards conversion, in particular, to decimate an input sequence of higher definition signals into an output sequence of lower definition signals. A suitable decimation filter is described in U.S. Patent No. 4,991,010, entitled "Dual-mode Image Interpolation Filter Operable in a First Mode for Storing Interpolation Coefficients and in a Second Mode for Effecting Television Standards Conversion at a Pixel Rate", which is incorporated herein by reference. If this capability is provided in the spatial interpolator 16, then it is necessary to provide a valid pixel signal from the controller 22 to the output image store 18 in order to identify the wanted output pixels. If decimation is not employed, basically all of the output pixels are valid.

The high definition output signal is applied to the image store 18, which includes a first framestore 18a and a second framestore 18b for storing two consecutive frames. Recalling now that the high definition signal to this point is a sequential signal, an interlace/interpolate controller 24 loads a video frame sequentially into one framestore while extracting video fields (of a previously loaded frame) in interlace format from the other framestore. A digital red, green, and blue high definition field signal is thus provided to the frame rate converter 20, which is

controlled by the interlace/interpolate controller 24 to interpolate every fifth field and pass the other fields without modification. The output of the frame rate converter 20 is then available for further use, which may include
5 immediate broadcast transmission or recording, e.g., on video tape(after suitable standards conversion or encoding, as necessary). In any event, such further use is not to be part of the present invention.

The frame rate converter 20 performs a linear
10 interpolation between fields as generally shown in the time sequence diagram of Figure 3. An output sequence consists of five television fields for every two input film frames (that is, for a conversion from 24 frames/second to 60
fields/second). The first two fields of the output sequence
15 are generated from the first input(film) frame by the usual interlace method; that is, the first field comprises the odd lines scanned from the first input frame, and the second field the even lines from the first input frame. Hence, fields 1 and 2 are displaced spatially by one line, but are
20 sampled from substantially the same point in time. Output field three, which could be considered the first of two fields of the second output(video) frame, is generated by interpolation. Specifically, each line of the interpolated output field consists of an unweighted interframe average of
25 the corresponding odd lines scanned from input(film) frames 1 and 2. The fourth and fifth output fields consist of the even and odd lines, respectively, from the second(film) frame. This process is then repeated for pairs of
input(film) frames over the remainder of the input frames.
30 Since the conversion is from an even number of input frames to an odd number of output fields, the lines used in the respective conversions, i.e., whether odd or even, will alternate for each five field sequence. Specifically, this means that the lines comprising every fifth interpolated
35 field will alternate field-by-field between interframe

averages of the odd lines and the even lines of two consecutive input frames.

The disclosed method is believed to be of particular advantage, for the following reasons:

- 5 (1) The level of motion judder artifacts should be considerably lower than when the "3,2" method is employed. There are two sources of motion judder artifacts: first, due to temporal field replication, and secondly due to the use of input frames for unequal time intervals in the output
10 sequence (as is the case in the "3,2" method, where the interval alternates between 1/20th and 1/30th second, respectively). The present invention resolves the latter problem by employing each input frame for an equal interval, 1/24th second, in the output sequence;
- 15 (2) Only every fifth output field suffers from artifacts due to the interpolation process, as opposed to every field in the case of full interpolation. Hence the interpolation algorithm can be very simple, e.g., linear
20 interpolation between two frames, and the resultant artifacts should not be perceptible; and
- (3) The cost of the implementation of this algorithm in hardware should be comparable with that of the "3,2" method, and significantly cheaper than either the full interpolation or motion-compensated methods.
- 25 The invention has been described in detail with particular reference to a presently preferred embodiment, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention.

What is claimed is:

1. Frame rate conversion apparatus for use in film scanning apparatus of the type wherein pixels relating to input images derived from consecutive frames (1,2) of film
5 are sampled at a predetermined rate related to a film scanning speed, and wherein output pixel information is converted to output fields (1,2,3,4,5) of a standard television signal, said frame rate conversion apparatus comprising:
 - 10 means (18) for storing input image pixel data corresponding to at least two frames (1,2) of film;
means (20,24) responsive to said storing means (18) for interpolating between image pixel data corresponding to selected input frames (1,2) to periodically generate an
15 output television field (3); and
means (20) responsive to said interpolating means for generating a standard television signal from the interpolated field (3) and the intervening uninterpolated fields (1,2,4,5).
- 20 2. Apparatus as claimed in Claim 1 wherein said interpolating means (20,24) performs a linear interpolation between image pixel data corresponding to two consecutive image frames (1,2).
3. Apparatus as claimed in Claim 2 wherein said
25 linear interpolation comprises an unweighted interframe average of corresponding lines from the two consecutive frames (1,2).
4. Apparatus as claimed in Claim 3 wherein the frame rate conversion involves converting from an even number of
30 input frames (1,2) to an odd number of output fields (1,2,3,4,5) and wherein corresponding lines being averaged for the interpolated fields (3) alternately comprise odd lines and even lines from two consecutive frames (1,2).
5. Apparatus as claimed in Claim 1 wherein the
35 interpolated field (3) is every fifth output field.

6. A method for converting between an input frame rate derived from scanning a motion picture film to an output field rate corresponding to a standard television signal, said conversion being from an even number of input frames (1,2) to an odd number of output fields (1,2,3,4,5),
5 said method comprising the steps of:

generating a first even number of output fields (1,2) from a first input frame (1);
interpolating an intermediate field (3) from the
10 first input frame (1) and a second input frame (2); and
generating a second even number of output fields (4,5) from the lines of a second input frame (2).

7. A method as claimed in Claim 6 wherein said conversion is from two input frames (1,2) to five output
15 fields (1,2,3,4,5), and wherein said intermediate field (3) comprises every fifth output field.

8. A method as claimed in Claim 7 wherein said output fields alternate between two five field sequences, and wherein in the first sequence said first even number of
20 output fields comprises a first field (1) and a second field (2) generated from the odd lines and the even lines of the first input frame (1), said second even number of output fields comprises a fourth field (4) and a fifth field (5) generated from the even lines and the odd lines of the
25 second input frame (2), and said intervening field (3) comprises an interpolation of the odd lines of both first and second input frames (1,2), and wherein in said second sequence said first even number of output fields comprises a first field (6) and a second field (7) generated from the
30 even lines and the odd lines of a third input frame (3), said second even number of output fields comprises a fourth field (9) and a fifth field (10) generated from the odd lines and the even lines of a fourth input frame (4), and said intervening field (8) comprises an interpolation of the
35 even lines of both third and fourth input frames (3,4).

9. A method as claimed in Claim 6 wherein the interpolation is an interframe average of corresponding lines from the input frames.

1/3




FIG.1

2/3




FIG. 2

3/3




FIG. 3

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)⁶

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 H04N7/01

II. FIELDS SEARCHEDMinimum Documentation Searched⁷

Classification System

Classification Symbols

Int.Cl. 5

H04N

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched⁸**III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹**

Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	EP,A,0 437 850 (SONY CORPORATION) 24. July 1991 see the whole document	6-9
Y	---	1-5
Y	US,A,5 045 932 (SHARMAN ET AL.) 3 September 1991 cited in the application see the whole document -----	1-5

¹⁰ Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

25 MAY 1993

Date of Mailing of this International Search Report

0 7. 06. 93

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

VERLEYE J.